

Boltaflex[®] Contract Upholstery

ColorGuard

Product Specifications:

General

Total Wt. - oz./sq. yd. (CFFA-700d)	24
Total Wt. - oz./lin. yd. (CFFA-700d)	36
Width (min.) - in. (CFFA-700a)	54"
Gauge (mils)	50
Face Content	PVC

Backing

Construction	Jersey Knit
Weight - oz./sq. yd.	3.0
Content	Polyester
Fiber Type	Spun

Adhesion (CFFA-3)

Pounds/Inches (min.)	Warp 3.0
	Fill 3.0

Tensile Strength (CFFA-17)

Pounds (min.)	Warp 110
	Fill 85

Trap Tear Strength (CFFA-16c)

Pounds (min.)	Warp 25
	Fill 25

Tack Strength (Stitch) (CFFA-14)

Pounds (min.)	Warp 60
	Fill 30

Performance Testing: meets or exceeds

Abrasion

Wyzenbeek, Wire Screen	60,000 cycles
Wyzenbeek, Cotton Duck	1 million cycles

Blocking (CFFA-4)

Pass

W-Flex (CFFA-10)

25,000 cycles

Crock (CFFA-7)

Pass

UV (CFFA-2)

QUV	650 hours (outdoors)
-----	----------------------

Mildew Resistance

ASTM G-21	Pass
AATCC 147	Pass

Cold Crack (CFFA-6a)

-20°F

Flame Retardancy

California Tech. Bulletin 117	Pass
NFPA 701 Small Scale	Pass
Fed. Std. A-A-2950 Supercedes CCC-A-680A	Pass
FAR 25.853A	Pass
Boston Fire Dept. IX-1	Pass
NFPA 260	Pass
NY/NJ Port of Authority	Pass
FMVSS-302	Pass
UFAC Fabric, Class 1	Pass

Miscellaneous:

Application

Indoor/Outdoor

Finish

PreFixx[®] Protective Coating



OMNOVA Solutions Inc. • Fairlawn, OH 44333 • www.omnova.com
contact us at upholstery@omnova.com

BOLTAFLEX and PREFIX are registered trademarks of OMNOVA Solutions Inc.
ALL OMNOVA PRODUCTS AND SERVICES ARE OFFERED AND SOLD SUBJECT TO THE OMNOVA
STANDARD TERMS AND CONDITIONS OF SALE AGREEMENT SET FORTH AT WWW.OMNOVA.COM
© 2010 OMNOVA Solutions Inc. QA#007-11-013 Rev.10 • 08/17/09